

Delta DY Push Travel Beam Trolley Specifications

| Model | Capacity (tonne) | Test Load (t) | Suitable Beam Width (mm) | Min. Radius (m) | Wheel Diameter (Radius MM) | Net Weight (kg) |
|--------|------------------|---------------|--------------------------|-----------------|----------------------------|-----------------|
| DY0500 | 0.5t | 0.63 | 50 – 305 | 0.5 | 55 | 5.4 |
| DY1000 | 1t | 1.25 | 58 – 305 | 0.7 | 68 | 9.3 |
| DY2000 | 2t | 2.5 | 66 – 305 | 0.9 | 80 | 14.8 |
| DY3000 | 3t | 3.75 | 74 – 305 | 1.2 | 100 | 24.1 |
| DY5000 | 5t | | 90 – 220 | | | 40 |
| | 5t | 6.25 | 90 – 305 | 1 | 120 | 41.1 |

| DIMENSIONS (mm) | | | | | | | | | |
|-----------------|-----|-----|----|-----|-----|-----|----|----|----|
| Capacity (t) | A | B | C | D | E | G | H | J | K |
| 0.5 | 198 | 68 | 40 | 94 | 82 | 385 | 28 | 25 | 13 |
| 1 | 238 | 82 | 31 | 102 | 85 | 388 | 37 | 29 | 17 |
| 2 | 277 | 95 | 31 | 119 | 99 | 405 | 48 | 36 | 20 |
| 3 | 324 | 116 | 31 | 139 | 113 | 429 | 56 | 46 | 26 |
| 5 | 354 | 373 | | | | | | | |

